

TEKNİK ÖZELLİKLER / TECHNICAL SPECIFICATION		DOEDA- 60-70-90-90-110-130		DOEDA- 60D-70D		DOEDA- 80D-90D-110D	
PISTON SAYISI / NUMBER OF PISTON		1		2		2	
PISTON ÇAPI ve KESME GRAMAJ ARALIĞI / PISTON DIAMETER and GRAMAGE RANGE		60 mm	40 - 160 gr	60 mm	40 -160 gr	80 mm	70 - 300 gr
		70 mm	50 - 200 gr			90 mm	80 - 360 gr
		80 mm	70 - 340 gr				
		90 mm	80 - 400 gr	70 mm	50 - 200 gr	110 mm	150 - 650 gr
		100 mm	150 - 650 gr				
		110 mm	300 - 1000 gr				
MAX. KESME KAPASİTESİ / MAX. CUTTING CAPACITY		max. 2000 pcs/h		max. 4000 pcs/h			
HAMUR BANT ÇIKIŞ YÜKSEKLİĞİ / DOUGH OUTPUT HEIGHT		89 - 100 cm					
BUNKER KAPASİTESİ / BUNKER CAPACITY		70 kg					
DIŞ ÖLÇÜLER (LxPxH) / EXTERNAL DIMENSIONS (LxPxH)		98x143x160		98x143x160		113x143x160	
KONTROL PANELİ / CONTROL SYSTEM		ELEKTROMEKANİK/DİJİTAL / ELEKTROMECHANIC/DIGITAL					
ELEKTRİK GÜCÜ / ELECTRICAL POWER		1,5 kw		2,2 kw		2,2 kw	
ELEKTRİK BAĞLANTI TÜRÜ / ELECTRICAL CONNECTION		380 V 50 Hz N+PE 3Phase					
AĞIRLIK / HEIGHT		450 kg		460 kg		570 kg	
www.refric.com.tr							